

Technical Specification - Rascal Razoo Powerchair

Wheelchair type – Rear Wheel Drive	Class A, B or C	EN 12184 - Class B
Department of Transport	Class 1, 2 or 3	Class 2
Overall dimensions fully assembled	length x width x height mm (in)	896 (35.3.) x 582 (22.9) x 1150 (45.3)
Dimensions- seat and footrest folded	length x width x height mm (in)	656 (25.8) x 582 (22.9) x 790 (31.1)
Maximum carrying capacity	Kg (lbs) ((stone))	136 (300) ((21.4))
Mass (weight) including 22Ah batteries	Kg (lbs)	57.9 (127.6)
Mass (weight) of heaviest part	Kg (lbs)	27.5 (60.6)
Mass (weight) of seat	Kg (lbs)	16.3 (35.9)
Battery voltage and capacity	Volts and Ampere-hours	12V / 22Ah x 2
Type of seat	Captain Rotating	Swivel, reclining, headrest with folding armrests
Drive Wheel dimensions	mm (in)	225 x 70 (9 x 2.75)
Castor Wheel dimensions	mm (in)	175 x 45 (7 x 1.75)
Type of wheels/ tyres	Type	Solid puncture proof
Maximum speed Rear-Wheel Drive	Km/h (m.p.h.)	6.1 (3.8)
Minimum braking distance at max. speed	m (ft)	0.85 (2.8)
Range*	Km (miles)	11.0 (6.8)
Turn-around width	m (ft)	0.97 (3.2)
Max. safe slope RWD	Degrees of slope	6° -Do not exceed Powerchair may topple
Max. climbing ability facing forward RWD	Degrees of slope	6°
Ground clearance	mm (in)	35 (1.4)
Max. obstacle climbing ability	mm (in)	40 (1.6)
Max. descendible kerb height	mm (in)	40 (1.6)
Force to operate Joystick Controller	Newtons (lbf)	1.0 (0.22)
Force to operate Freewheel levers	Newtons (lbf)	45 (10.1)
Ambient operating temperature range	°C (°F)	2 (35.6) to 40 (104)

NOTE: This Powerchair meets the relevant requirements of ISO 7176-14 :2008

*Range on full charge and flat ground to ISO 7176-4:2008

Due to a policy of continual improvement, Electric Mobility Euro Ltd. reserves the right to change specifications without prior notice.